

GENERAL INFORMATION LEAFLET

Product Information: Unicoatings™ UC WAX COAT

Unicoatings™ UC WAX COAT is a semi-permanent coating system. When applied to glass fibre GFK, metals, plastics and painted surfaces, the treated surfaces deflect water, oil and dirt and are much easier to keep clean.

UC WAX COAT is a clear coating that contains no abrasive ingredients. When applied to new or optically finished surfaces, the product gives those surfaces a glossy shine and forms a protective barrier against soiling by dirt or dust.

TECHNICAL DATA

Water-based suspension with care additives.

APPLICATION

- Do not dilute the product. The surface to be treated should be clean and free from any oils or greases
- Test the product on a small section of the surface to be treated to ensure suitability
- Apply a small amount of UC WAX COAT using a clean duster or cotton cloth. Apply thinly and cover the whole surface area
- Leave for at least 15-20 minutes (maximum 60 minutes) to allow a film to become visible, and then polish off this film using a soft cloth. A longer drying time can improve the effect.
- After a further 1 hour, the chemical binding process on the treated surface will be complete
- Following treatment, treated surfaces can easily be kept clean from dust and dirt by simply wiping with a damp cloth or sponge
- Do not apply any waxes to a treated surface
- When the effect of the polish eventually wears off, simply refresh by the method outlined above

PACKAGING

UC WAX COAT is available in 250ml bottles, 1-litre bottles or 5-litre canisters. For bulk orders please contact Unicoatings.

STORAGE

UC WAX COAT can be stored for at least 12 months in its original packaging. Protect from frost and direct sunlight.

DISPOSAL

Empty bottles and canisters, as well as any remaining product, must be disposed of in accordance with your country's laws and regulations.

SAFETY / PROTECTION MEASURES

When using UC WAX COAT please follow the instructions on the bottle / canister. The use of chemical preparations should only take place when the safety measures are observed and are always out of the reach of children. The technical information provided here is in accordance with the latest technical knowledge and composed from our own experience. In view of the many uses possible with UC WAX COAT, it is therefore the responsibility of the user to act according to the given situation in respect of safety. As the use of this product takes place out of our jurisdiction, we have set out safety and protection measures, but we cannot be held responsible in any circumstances. For any misuse of the product we cannot be held responsible. In the event of a new version of this information becoming available, this information here set out is no longer valid.

All information on our products can be found on our website: www.unicoatings.com